

Compact 3 Ton 3.5 Tons Lpg Forklift Trucks Hydraulic Automatic Transmission

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Goodsense
- Model Number: FG25
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T



Product Specification

- Model Number: FG25 FG30 FG35
- Rated Loading Capacity: 2.5 TON 3 Ton 3.5 TON
- Core Components: Pump, Gearbox, Engine
- Weight (KG): 4300 Kg
- Fork Length: 1070mm
- Fork Width: 125mm
- Overall Dimensions: 1070*125*45mm
- Rated Capacity: 3000kg
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise
- Highlight: compact lpg gas forklift,



More Images



for more products please visit us on rdforklift.com

PRODUCT DETAILS

GOODSENSE 3 ton LPG forklift trucks bring power, dependability, productive forces and a low cost of property to operations across industry.

With a conventional automotive layout, GOODSSENSE 3 ton LPG forklift trucks are easy to use, simple to service and come with a range of standard characteristics and added choices.

With lift heights up to 6000mm, lift capacities from 1,500kg up to 3,000kg, empty load travel speeds up to 20km/h and excellent mobility, control and visibility, GOODSSENSE 3 ton LPG forklift trucks adapt to the needs of various businesses such as constructors, retailers, manufacturers, logistics, warehousing and much more.

Model			FF GG 22 05	FG30	FG35
Power Type			LL PP GG	LPG & Gasoline	LPG & Gasoline
Rated Capacity		kg	22 05 00 00	3000	3500
Load Centre		mm	55 00 00	500	500
Lift Height		mm	33 00 00 00	3000	3000
Fork Size	L×W×T	mm	11 00 77 00 ×× 11 22 00 ×× 44 00	1070×125×45	1070×125×50
Mast Tilt Angle	F/R	Deg	66 °/°/ 11 22 °°	6°/12°	6°/12°
Front Overhang (Wheel center to fork face)		mm	44 44 55	480	485
Ground Clearance(Bottom of mast)		mm	88 00	140	140
Overall Dimension	Length to face of fork(Without fork)	mm	22 33 55 55	2730	2775
	Overall Width	mm	11 11 11 00	1225	1225
	Mast Lowered Height	mm	22 00 77 00	2115	2115

	Mast Extended Height(With backrest)	mm	44007700	4150	4150
	Overhead Guard Height	mm	22008800	2090	2090
Turning Radius (outside)		mm	22111100	2440	2480
Speed	Travel (Full load)	km/h	1177	20	20
	Lifting (Full load)	mm/s	553300	510	440
Max.Gradeability (No load/Full load)		%	2200	20	20
Tire	Front	mm	2211**77**1155	28×9-15-12PR	28×9-15-12PR
	Rear	mm	1166(1/1/4)**66**111(1/1/4)	6.50-10-10PR	6.50-10-10PR
Wheelbase		mm	11440000	1700	1700
Service weight		kg	33464555	4300	4500
Battery	Voltage/Capacity	V/Ah	112/2/8800	12/80	12/80
Engine	Model		K25EP A	K25	
	Manufacture		GCT (NISSAN)	GCT (NISSAN)	
	Rated output/r.p.m.	kw	42/2700	35.6/2100	
	Rated torque/r.p.m.	N·m	185/1350	176.5/1600	
	No.of Cylinder		4	4	
	Bore×Stroke	mm	89×100	89×100	
	Displacement	cc	2488	2488	
	Fuel Tank Capacity	L	55	60	60

Transmission	Type		Hydraulic	Hydraulic
	Standard FWD/RVS		1/1	1/1



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjg_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China